

# DuPont™ Cyrel® DPN

MEDIUM HARD CYREL® DIGITAL PLATE WITH HIGHEST POSSIBLE RESOLUTION

## DuPont Packaging Graphics

**To help our customers gain competitive advantage in the global packaging graphics value chain.**

DuPont Packaging Graphics continues to be a global technology leader in supplying flexographic printing systems. Our scientists continue to develop unique solutions based on new technologies to help our customers expand their business by taking advantage of new profitable packaging printing opportunities. DuPont Packaging Graphics portfolio of products includes Cyrel® brand photopolymer plates (analogue and digital), Cyrel® platemaking equipment, Cyrel® round sleeves, Cyrel® plate mounting systems and the revolutionary Cyrel® FAST thermal system.


**Cyrel® DPN is a digital plate that offers the highest resolution of all digital plates and it offers very good ink compatibilities for solvent and UV inks.**

### Applications

- Flexible packaging
- Tag & Label
- Folding cartons
- Beverage cartons

### Product Features

- Excellent ink transfer permits superior printing uniformity
- Highest available exposure resolution
- Image relief is clean and sharp
- Finest text and lines with open reverses



## DuPont™ Cyrel® DPN

- Exceptional thickness uniformity
- Less make ready time
- High resistance to ozone and white light results in excellent storage capability

### Printing ink and solvent compatibility

Cyrel® DPN offers excellent compatibility with UV, solvent-based and water-based inks.

### Process of use

Expose the plate through the back to establish the floor and maximize sensitivity. Back exposure varies according to relief required. Remove the protective coversheet and image the plate with the Cyrel® Digital Imager (CDI). Expose the

front of the plate surface. Process the plate in the Cyrel® solvent processor to remove unexposed polymer. Finish the plate in a light finisher to eliminate surface tackiness.

### Mounting

Cyrel® Microflex mounting devices are recommended for mounting Cyrel® DPN plates. The double sided adhesive should first be applied to the cylinder or sleeve – not the plate – to ensure easier and precise laydown. The polyester base will maintain accurate register even with large plates.



*The miracles of science™*

### Storage – Raw Material

Store unexposed plates in a cool area (4-32° C), away from direct sources of heat. Humidity control is not required. Cyrel® DPN is foam interleaved to provide maximum protection of the plate after manufacture, and during transportation and storage. Plates should be stacked flat. Plates should not be

exposed to direct sunlight or excessive white light. Continuous exposure to very high ozone concentrations should be avoided.

### Handling – Raw Material

Cyrel® DPN plates should be handled under UV free light; e.g. fluorescent tubes covered with amber sleeves.

### Storage – Finished Plates


After printing, plates should be thoroughly cleaned with compatible solvent before storing. They may be stored on cylinders, sleeves or demounted and stored flat.

<b>Technical Data</b>				
	<b>Cyrel® DPN 45 Thickness 1.14 mm/ 0.045 inch</b>	<b>Cyrel® DPN 67 Thickness 1.70 mm/ 0.067 inch</b>	<b>Cyrel® DPN 100 Thickness 2.54 mm/ 0.10 inch</b>	<b>Cyrel® DPN 112 Thickness 2.84 mm/ 0.112 inch</b>
<b>Durometer</b>	76 Sh A	67 Sh A	56 Sh A	54 Sh A
<b>Image Reproduction</b>	1 – 98% 60 L/cm	1 – 98% 60 L/cm	1 – 98% 54 L/cm	1 – 98% 54 L/cm
<b>Minimum positive line width</b>	0.050 mm/ 2 mil	0.050 mm/ 2 mil	0.075 mm/ 3 mil	0.075 mm/ 3 mil
<b>Minimum isolated dot size</b>	200 µm	200 µm	250 µm	250 µm
<b>Relief Depth</b>	0.60 mm/ 0.024 inch	0.70 mm/ 0.028 inch	0.80 mm/ 0.031 inch	0.90 – 1.00 mm/ 0.035 – 0.039 inch

*All technical information set out herein is provided free of charge and is based on technical data, which DuPont believes to be reliable. It is intended for use by persons having skill, at their own discretion and risk. The handling precaution information contained herein is given with the understanding that those using it will satisfy themselves that their particular conditions of use present no health or safety hazards. Since conditions of product use are outside of our control we make no warranties express or implied in relation thereto and therefore cannot accept any liability in connection with any use of this information. Nothing herein is to be taken as a license to operate under, or a recommendation to infringe any patents.*

Du Pont de Nemours (Deutschland) GmbH  
DuPont Imaging Technologies  
Hugenottenallee 173  
63263 Neu-Isenburg  
Deutschland  
Tel: +49 (0) 6102 18 3324

Du Pont (U.K.) Limited  
DuPont Imaging Technologies  
Wedgwood Way, Stevenage  
Hertfordshire SG1 4QN  
United Kingdom  
Tel: +44 (0) 1438 734485



To learn more, visit [www.packaging-graphics.dupont.com](http://www.packaging-graphics.dupont.com)  
or contact your Cyrel® specialist



*The miracles of science™*

**DuPont Packaging Graphics**  
**“Advancing Flexography”**